

SUBWOOFER



Total Pieces	1
Height	18.5" (46.99 cm)
Width	17.126" (43.5 cm)
Depth	18.1" (46 cm)
Weight	49.9 lbs (22.63 kg)
Subwoofer Array Driver Enclosure Type	Power Port Bass Vented
Subwoofer Array Driver Complement	•(1) 12" (30.48 cm) d (Round) Polypropylene Dynamic Balance and Klippel optimized driver - Subwoofer
Peak Power	400 Watts
Continuous Power	200 Watts
Amplifier Class	Class D
Total Frequency Response	22 Hz → .180 Hz
Nominal Impedance	8 ohms
Lower and Upper -3dB Limits	28 Hz → .120 Hz
IO Button Location	Back Panel
Adjusts	•Volume +/- •Low Pass Filter (40Hz-160Hz) •Phase (0/180°) •Power: Auto on/off •Power: DC control (12V trigger)
Audio Inputs	•LFE (Unfiltered) •Stereo Line Level - (2) RCA
US Power Cycle	Energy Star Compliant with Auto Standby (.5W)

HTS 12 SUBWOOFER



Total Pieces	1
Height	18.5" (46.99 cm)
Width	17.126" (43.5 cm)
Depth	18.1" (46 cm)
Weight	49.9 lbs (22.63 kg)
Subwoofer Array Driver Enclosure Type	Power Port Bass Vented
Subwoofer Array Driver Complement	•(1) 12" (30.48 cm) d (Round) Polypropylene Dynamic Balance and Klippel optimized driver - Subwoofer
Peak Power	400 Watts
Continuous Power	200 Watts
Amplifier Class	Class D
Total Frequency Response	22 Hz → .180 Hz
Nominal Impedance	8 ohms
Lower and Upper -3dB Limits	28 Hz → .120 Hz
IO Button Location	Back Panel
Adjusts	•Volume +/- •Low Pass Filter (40Hz-160Hz) •Phase (0/180°) •Power: Auto on/off •Power: DC control (12V trigger)
Audio Inputs	•LFE (Unfiltered) •Stereo Line Level - (2) RCA
US Power Cycle	Energy Star Compliant with Auto Standby (.5W)

SIGNATURE ELITE ES15 BOOKSHELF



Availability	US Internationally
Qty Included	Pair
Width	7.5" (19.1 cm)
Height	12" (30.48 cm)
Weight	13 lbs (5.9 kg)
Depth	10.2" (25.9 cm)
Orientation	Horizontal
Front Array Driver Complement	<ul style="list-style-type: none">• (1) 1" (2.54 cm) d (Round) Terylene High-Res Dome Tweeter• (1) 5.25" (13.34 cm) d (Round) Dynamic Balance Mica Reinforced Polypropylene Driver
Impedance	Compatible with 8 ohm outputs
Mounting Type	Key hole slot
Max Sensitivity (1 watt @ 1 meter)	88dB
Recommended Amplifier Power Per Channel	20 watts → 100 watts
Crossover Frequency	2500 Hz
Total Frequency Response	48 Hz → 40,000 Hz
Inputs	Single gold-plated 5-way binding posts

SIGNATURE ELITE ES30 CENTER



Qty Included	1
Width	20" (50.8 cm)
Height	7.5" (19.05 cm)
Depth	10.6" (26.92 cm)
Weight	19 lbs (8.62 kg)
Orientation	Horizontal
Driver Complement	<ul style="list-style-type: none">• (1) 1" (2.54 cm) d (Round) Terylene High-Res Dome Tweeter• (2) 5.25" (13.34 cm) d (Round) Dynamic Balance Mica Reinforced Polypropylene Drivers
Driver Enclosure Type	PowerPort Bass Vented
Impedance	Compatible with 4 and 8 ohm outputs
Recommended Amplifier Power Per Channel	20 watts → 150 watts
Inputs	Single gold-plated 5-way binding posts
Max Sensitivity (1 watt @ 1 meter)	89 dB
Crossover Frequency	2500 Hz
Total Frequency Response	55 Hz → 40,000 Hz

SIGNATURE ELITE ES55 TOWER X2



Qty Included	1
Width	8.5" (21.6 cm)
Height	41.5" (105.41 cm)
Depth	12.5" (31.75 cm)
Weight	44 lbs (19.96 kg)
Front Array Driver Complement	1 x (1) 1" (2.54 cm) d (Round) Terylene High-Res Dome Tweeter • (2) 6.5" (16.51 cm) d (Round) Dynamic Balance Mica Reinforced Polypropylene Drivers
Driver Enclosure Type	Power Port Bass Vented
Width with Base	11.7" (29.7 cm)
Impedance	Compatible with 4 and 8 ohm outputs
Sensitivity (1 watt @ 1 meter)	90 dB
Crossover Frequency	2,500 Hz
Total Frequency Response	40 Hz → 40,000 Hz
Type	2-way
Recommended Amplifier Power Per Channel	20 watts → 200 watts
Inputs	Dual gold-plated 5-way binding posts